

# HP 602030 LFP

## 36 Ah/ 116 Wh

### Prototype Datasheet

#### Physical and mechanical characteristics

Diameter	60 mm
Height	232 mm (203 mm without terminals)
Terminals	Positive terminal Al M12 L: 9 mm Negative terminal Cu M12 L: 9 mm
Weight	approx. 1450 g
Volume without terminals	0.57 l
Case material	Stainless Steel

#### Chemical characteristics

Positive electrode	Lithium iron phosphate
Negative electrode	Graphite

#### Electrical characteristics\*

Nominal voltage	3.2 V
Nominal capacity at 0.2 C	36 Ah
Minimum capacity	34 Ah
AC Impedance (1 kHz)	$\leq 0.5 \text{ m}\Omega$
DC Resistance (ESR) (2 s pulse discharge @ 20 C/ 50% SOC)	$\leq 1 \text{ m}\Omega$
Specific energy at 0.2 C	79 Wh/kg
Energy density at 0.2 C	201 Wh/l
Specific power (2 s pulse discharge @ 25 C/ 100% SOC)	1550 W/kg
Power density (2 s pulse discharge @ 25 C/ 100% SOC)	3920 W/l

#### Operating conditions\*

Recommended charge method	Constant current - constant voltage
End of Charge	$I \leq C/10$
Maximum charge voltage	3.8 V
Recommended charge current	up to 36 A (1 C)
Continuous charge current	up to 144 A (4 C)
Maximum pulse charge current (10 s) (Max. SOC 70 %, average current < 144 A)	216 A (6 C)
Recommended voltage limit for discharge	2.5 V
Lower voltage limit for discharge	2.1 V
Lower voltage limit for pulse discharge	2 V
Recommended discharge current	up to 72 A (2 C)
Maximum discharge current	up to 360 A (10 C)
Maximum pulse discharge current (2 s)	up to 900 A (25 C)
Operating temperature	- 15°C to + 60°C
Recommended charge temperature	0°C to + 40°C
Storage and transport temperature	- 40°C to + 60°C
Cycle life at 20°C and 100% DOD (0,5 C charge; 0,5 C discharge)	> 1000 cycles to 80% nominal capacity > 2000 cycles to 60% nominal capacity

\* Reference temperature 20°C

Doc HP 602030 LFP - 2009-11

Data in this document are subject to change without notice and are not binding.